

### Parallel vice

With forged and hardened pipe jaws, steel forged underneath the parallel vice jaws

- Non-breakable
- Protected, powerful spindle with trapezoidal thread
- Re-adjustable double-sided guide
- Anvil base for levelling and compressing work



Jaw width mm	Clamping width mm	depth mm	for pipes Inch	for pipes mm	kg	No.
120	125	65	3/8 - 1.1/2"	16 - 55	8.7	<b>070705X</b>
140	150	80	3/4 - 2"	27 - 70	15.6	<b>070735X</b>

### Pipe vice

Foldable, with automatic closing hook, upper jaw and lower support jaw milled and hardened. Powerful smooth-running spindle. Durable epoxy-powder coated

- Reliable hold: Pipe support and movable upper jaw



For pipes / inch	for pipes / mm	kg	No.
1/8 - 2"	10 - 60	3.7	<b>70710</b>
Spare jaws (contains: 3 pcs.)		0.2	<b>70670</b>
1/8 - 3"	10 - 89	7.9	<b>70712</b>
Spare jaws (contains: 3 pcs.)		0.2	<b>70672</b>
1/8 - 4"	10 - 114	11.7	<b>70711</b>
Spare jaws (contains: 3 pcs.)		0.2	<b>70671</b>

### Chain pipe vice

Tough, powerful design with V-shaped support, bending device, pipe support, wear-resistant jaws are forged and hardened, powerful chain, quick fastening due to offset lever and pre-tensioning screw, simple conversion to other pipe diameters, extremely robust powder epoxy coating

- V-shaped pipe supports with teeth and bridge prevent undesired bending during clamping
- Exchangeable jaws



For pipes / Inch	for pipes / mm	kg	No.
1/8 - 2.1/2"	10 - 76	3.8	<b>70713</b>
Spare jaw		0.7	<b>70734</b>
Spare chain		0.5	<b>70731</b>
1/8 - 4"	10 - 114	6.2	<b>70714</b>
Spare jaw		0.8	<b>70721</b>
Spare chain		0.6	<b>70732</b>
1/8 - 6"	10 - 165	9.3	<b>70715</b>
Spare jaw		0.9	<b>70722</b>
Spare chain		1.3	<b>70733</b>

### ROBOY clamping workbench

For on-site repair and service work

- Portable, handy and practical workbench with the smallest dimensions
- Mountable on door frames or walls: Prevents floor damage and saves space
- Pressure plate is coated with rubber to protect against damage
- Spindle with trapezoidal thread for quick adjustment
- With height-adjustable support pipe for additional stability



Parallel vice (No. 070705X) and rotatable table not included

Model	Dimensions / mm	kg	No.
ROBOY	650 x 400	14.9	<b>70700</b>