Mini Contact Thermometer

G9400 Series - G9402

The GAZELLE G9402 Mini Contact Thermometer is a dual-input digital thermometer that delivers a fast response. Designed to measure two contact temperature inputs simultaneously, whether measuring motors, insulation, pipes, liquids, and wires with industrial standard J, K-type thermocouple temperature sensors. The user friendly-front panel and large, backlit display make it easy to view results from both channels.











- 1m drop proof
- Maximum/minimum/average
- Big LCD display with bright white backlight for a clear view of measurement
- K/J thermocouple probe selection
- Difference measurement: T1~T2
- CE Certified

Standard Accessories

- Operating Manual
- Temperature Probe
- 1.5V AAA 3pcs

| Specifications | Ran | ge | Best Accuracy |
|--------------------------------|------------|--------------|---------------|
| Temperature measurement (K) | -50~1300°C | | ±(0.5%+1) |
| Temperature measurement (J) | -50~1200°C | | ±(0.5%+1) |
| Features | | | |
| Difference measurement (T1-T2) | | \checkmark | |
| Unit conversion (°C/°F) | | \checkmark | |
| Max/Min/Avg | | | |
| Function selection (K/J) | | | |
| Backlight | | V | |
| Working temperature | | 0°C~40°C | |
| Working humidity (relative) | | ≤80%RH | |
| 1m drop test | | | |
| Power | | 3 x AAA | |

www.gazelleindustrial.com **TEST & MEASUREMENT SOLUTION**