



D25733K-B5

SDS Max Comb. Hammer w/ UTC 48mm
7kg 220V

FEATURES

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 48 mm in diameter. Core drilling up to 125 mm
- Active vibration control system incorporating a counterbalance mass and floating handle delivers extremely low vibration
- An anti rotation system detects a loss of tool control, and reacts by instantly cutting the power
- 2 stage clutch system that allows the user to change the clutch level from low to high torque, to optimize the tool for specific drilling applications
- Electronic speed and impact energy control
- Lock-on switch for chipping
- Rotation-stop for demolition applications in brick, masonry and light chasing in concrete
- Brush wear and service indicators

SPECIFICATIONS

Tool Holder	SDS-Max
Power Input	1400 Watts
Power Output	840 Watt
Impact energy (EPTA 05/2009)	11 J
Load Speed	137-275 rpm
Blows per Minute	1260-2520 bpm
Max. Drilling Capacity [Concrete]	48 mm
Max. Drilling Capacity [Breakthrough bit]	80 mm
Max. Drilling Capacity [Core bit]	125 mm
Weight	9.1 kg
Length	528 mm
Height	268 mm
Width	116 mm
Hand/Arm Vibration - Hammer drilling into concrete	7.5 m/s ²
Uncertainty K 1 (Vibration)	1.5 m/s ²
Hand/Arm Vibration - Chiseling	6.9 m/s ²
Uncertainty K 2 (Vibration)	1.5 m/s ²
Sound Pressure	95 dB(A)
Sound Pressure Uncertainty	3 dB(A)
Sound Power	106 dB(A)
Sound Power Uncertainty	4 dB(A)