

### GAZELLE G9202, G9203 600A True RMS Digital Clamp Meter

The Gazelle G9202, G9203 clamp meter is the right tool to diagnose a wide range of electrical issues in commercial and industrial applications. Capable to True RMS measurements, AC DC voltage, AC Current, Resistance, Capacitance and Frequency measurement to fulfill the needs of daily test and measurements requirements. The tool is ergonomic designed and features a large backlight display for efficient troubleshooting.



- TRMS measurement AC-DC Voltage and AC current measurement
- Multi function capable for Resistance, Diode, Continuity, Frequency measurements
- 600A full range overload protection for additional safety
- CAT II 1000V / CAT III 600V safety rating
- Big LCD display Clear white backlight for measurement in dark areas
- Includes a built in torch for dark electrical panel
- NCV voltage detectors for safety verification
- Includes Gazelle branded carrying case



Specifications	G9202		G9203	
	Range	Best Accuracy	Range	Best Accuracy
AC Current (A)	4A/40A/400A	±(1.8%+9)	6A/60A/600A	±(2.5%+5)
AC Voltage (V)	4V/40V/400V/600V	±(1.2%+5)	6V/60V/600V/750V	±(1.2%+5)
DC Voltage (V)	400mV/4V/40V/400V/600V	±(0.8%+1)	600mV/6V/60V/600V/1000V	±(0.8%+1)
Resistance (Ω)	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1.0%+2)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(1%+2)
Capacitance (F)	50nF/500nF/5μF/50μF/100μF	±(4.0%+5)	99.99nF/999.9nF/9.999μF/99.99μF/999.9μF/9.999mF/60mF	±(4.0%+5)
Frequency	10Hz-1MHz	±(0.1%+4)		
<b>Features</b>				
Auto Range	✓		✓	
Jaw Capacity	30mm		30mm	
Diode Around	1.5V		Around 3.0V	
NCV	✓		✓	
Data Hold	✓		✓	
Relative Mode	✓		✓	
LCD Backlight	✓		✓	
Flashlight	✓		✓	
Auto Power Off	✓		✓	
Continuity Buzzer	✓		✓	
Low Battery Indication	≤2.4V		≤3.6V	
Input Protection	✓		✓	
Input Impedance for DCV	≥10MΩ		≥10MΩ	

#### Standard Accessories

- Operating Manual
- Test Lead
- Carrying Case

